

The NetBackup Flex Deployment Mode on the 5350 Appliance



Consolidate NetBackup data protection in the enterprise core.

OVERVIEW

Data protection in the central data center requires the capacity and performance to support the most demanding workloads. The Veritas NetBackup™ Flex deployment mode running on the 5350 Appliance with its 2-PB capacity, ransomware resiliency, high availability, 25-Gb Ethernet and 16-Gb Fibre Channel I/O provides a robust, cost-effective solution for the enterprise core.

Based on container technology, the Flex deployment mode extends NetBackup data protection with multitenant capabilities to reduce data center costs, improve management efficiency and protect against ransomware and security threats.

SOLUTION HIGHLIGHTS

Ransomware resiliency.

The Flex deployment mode delivers new levels of security and ransomware resiliency, with policy-based immutable storage providing confidence in rapid recovery from ransomware attacks without specialized or dedicated storage hardware.

Reduce costs with consolidation.

Consolidate multiple NetBackup deployments on a 5350 Appliance with the multitenant capabilities of the Flex deployment mode. Drastically reduce the number of server and storage devices requiring setup, management, maintenance, power, cooling, cabling and floor space—significantly reducing data center costs.

Fibre Channel support available with the Flex deployment mode provides the capability to consolidate multiple NetBackup tape deployments on a 5350 Appliance.

NetBackup Flex Application Instances
NetBackup primary server
NetBackup media server with advanced disk storage pool
NetBackup media server with deduplication pool and cloud option
NetBackup WORM Storage Server

On-demand response to rapidly changing business environment.

Rapidly deploy infrastructure by configuring application instances into a complete data protection solution. Build systems to meet the specific information needs of a department or business unit.

Improve uptime with high availability.

High availability provides efficient use of hardware resources in normal operating conditions and higher uptime in case of failure. In a high-availability configuration, the 5350 Appliance running Flex distributes application instances across two nodes. In the event of failure, you can restart the application instances in the surviving node. The ability to relocate an application instance from one node to another allows for greater control and efficiency in managing preventive maintenance.

Proactive monitoring with NetInsights Console.

Monitors key hardware components and notifies the administrator of fault events.

PERFORMANCE	NETBACKUP FLEX 5350
Server Side Deduplication with 98% dedupe rate	54 TB/hr

TECHNICAL SPECIFICATIONS	NETBACKUP FLEX 5350 APPLIANCE	NETBACKUP FLEX 5350 APPLIANCE HIGH AVAILABILITY CONFIGURATION	STORAGE SHELF
Number of server nodes	1	2	NA
Minimum system usable capacity (TB) ¹	120 TB	120 TB	NA
Storage shelf usable capacity (TB) ¹	NA	NA	120, 240, or 480 TB (Dependent on number and capacity of drives installed in shelf)
Storage shelves (max)	4	4	NA
Max system usable capacity (TB) ¹	1.92 PB	1.92 PB	NA
1-Gb Ethernet ports	4	4 per compute node, (2 used for internode communication)	NA
25-10-Gb Ethernet ports	2-8	4-16	NA
16-Gb Fibre Channel ports	Up to 6	Up to 12	NA
Server Node & Storage Shelf dimensions H x W x D (inches)/(cm)	(3.5 x 19.0 x 30.5) / (8.9 x 48.3 x 7.9)	(3.5 x 19.0 x 30.5) / (8.9 x 48.3 x 76.9)	(8.75 x 19.0 x 36.75) / (22.3 x 48.3 x 93.3)
Max weight per component, with disk drives (lbs/kg)	43 / 19.5	43 / 19.5 ²	282/131
Typical power consumption (watts)	350	700 ²	1,047
Max power consumption (watts)	650	1,300 ²	1,243
AC voltage range (Volts) (Compute node voltage is auto-ranging)	90 to 140 180 to 264	90 to 140 180 to 264	200 to 240
AC frequency range (Hz)	47 to 63	47 to 63	50 to 60
Max ampere ratings (A)	3.03 (200V to 240V)	3.03 (200V to 240V)	5.65 (200V to 240V)

ENVIRONMENTAL SPECIFICATIONS	NETBACKUP FLEX 5350 APPLIANCE	NETBACKUP FLEX 5350 APPLIANCE HIGH AVAILABILITY CONFIGURATION	EXPANSION SHELF
Operating Temperature (°F)/(°C)	(50 to 95) / (10 to 35)	(50 to 95) / (10 to 35)	(41 to 95) / (5 to 35)
Storage Temperature (°F)/(°C)	(-40 to 158) / (-40 to 70)	(-40 to 158) / (-40 to 70)	(-40 to 158) / (-40 to 70)
Operating Humidity	10 to 80%	10 to 80%	10 to 80%
Operating altitude (ft)/(m)	(100-9,842) / (30.5-3,000)	(100-9,842) / (30.5-3,000)	(-328-9,842) / (-1000-3,000)
Max noise (dBA)	82	82	82
Typical Cooling (BTU/hr)	1,024	2,047	3,573
Max cooling (BTU/hr)	2,047	4,094	4,241

WARRANTY COVERAGE

One (1) year parts replacement and 90 days software.

MANAGEMENT

Through existing NetBackup Graphical User Interface.

PROTOCOL STANDARDS FOLLOWED

IPMI 2.0, SMBIOS 2.5, SAS 2.0a, ACPI rev 3, IP RFC0791

SAFETY AND EMC STANDARD COMPLIANCE

GB4943-2001, IEC 60950-1, UL 60950-1, FCC 47 CFR Part 15 Subpart A, EN 60950-1, EMC Directive 2004/108/ EC, EN 55024: 1998+A1+A2, LVD Directive 2006/95/EC

1. Capacity values are calculated using Base2, (i.e. 1 TB = 1,099,511,627,776 bytes).

2. Two server nodes in each configuration.

ABOUT VERITAS

Veritas Technologies is a global leader in data protection and availability. Over 50,000 enterprises—including 87 percent of the Fortune Global 500—rely on us to abstract IT complexity and simplify data management. The Veritas Enterprise Data Services Platform automates the protection and orchestrates the recovery of data everywhere it lives, ensures 24/7 availability of business-critical applications, and provides enterprises with the insights they need to comply with evolving data regulations. With a reputation for reliability at scale and a deployment model to fit any need, Veritas Enterprise Data Services Platform supports more than 800 different data sources, over 100 different operating systems, more than 1,400 storage targets, and more than 60 different cloud platforms. Learn more at www.veritas.com. Follow us on Twitter at [@veritastechllc](https://twitter.com/veritastechllc).

2625 Augustine Drive, Santa Clara, CA 95054
+1 (866) 837 4827
www.veritas.com

For specific country offices and contact numbers, please visit our website.
www.veritas.com/company/contact

VERITAS

Copyright © 2021 Veritas Technologies LLC. All rights reserved. Veritas, the Veritas Logo, and NetBackup are trademarks or registered trademarks of Veritas Technologies LLC or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners.

V1319 05/21